

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (1.3-1.5KW)

Model	XQ-1.3H	XYQ-1.5-5H	XYQ-1.5-6H	XYQ-1.5-7H
R.P KW	1.3	1.5		
R.V V	24	36		
R.C A	70	54	56	
R.P.M	1900	2800	1500	
Rating Min	60			
Protection Lv.	IP44			
Application	Electric Tricycle	2-4Seats Tour-Bus, Patrol-Car		
Structure Features(Shaft Extension & Connection)	Cylindrical($\Phi 19 \times 30$)	Concave Extension without end cover, 19-tooth Inch Internal Spline	Square Flange Connection, Internal Spline(m=1,z=18)	

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (2.2KW)

Model	XQ-2.2-7H3	XQ-2.2-9H3	XQ-2.2-10H2
R.P KW	2.2		
R.V V	36		
R.C A	78		
R.P.M	2800	2200	
Rating Min	60		
Protection Lv.	IP44		
Application	2-4Seats Tour-Bus, Patrol-Car		
Structure Features(Shaft Extension & Connection)	Concave Extension without end cover, 19-tooth Inch Internal Spline	Square Flange Connection, Internal Spline(m=1,z=18)	

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (3KW I)

Model	XQ-3-1H	XQ-3-1AH	XQ-3-1BH	XQ-3-1EH
R.P KW	3			
R.V V	45			
R.C A	87			
R.P.M	1780			
Rating Min	60			
Protection Lv.	IP20			
Application	2-4Seats Tour-Bus, Patrol-Car			
Structure Features(Shaft Extension & Connection)	Spline(6-20×16×4)	Φ 230End cover Flange Connection, Spline(6-20×16×4)	Horizontal with foot base, Spline(6-25×21×5)	Square Flange Connection, Internal Spline(m=1,z=18)

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (3KW II)

Model	XQ-3-5H3	XQ-3-6H1	XQ-3-6AH	XQ-3-6H3V	XQ-3-8H	XQ-3.8HV
R.P KW	3					3.8
R.V V	48					
R.C A	78			76		95
R.P.M	2800					3100
Rating Min	60					
Protection Lv.	IP44	IP20			IP44	
Application	4-8Seats Tour-Bus, Sanitation Truck				ATV, 6-8Seats Tour-Bus	6-8Seats Tour-Bus
Structure Features(Shaft Extension & Connection)	Concave Extension without end cover, 19-tooth Inch Internal Spline	Square Flange Connection, Internal Spline(m=1,z=18)	Round Flange connection, Spline (6-20×16×4)	Square Flange Connection, Internal Spline (m=1,z=18), With Speed sensor	Concave Extension without end cover, 19-tooth Inch Internal Spline	

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (4KW I)

Model	XQ-4HV	XQ-4HUV	XQ-4AH2V	XQ-4BH	XQ-4GHV
R.P KW	4				
R.V V	48				
R.C A	101		98		101
R.P.M	2800		2640		2800
Rating Min	60				
Protection Lv.	IP44				
Application	6-8Seats Tour-Bus, ATV, 2-4Seats Hunting-Car				
Structure Features(Shaft Extension & Connection)	Concave Extension without end cover, 19-tooth Inch Internal Spline, With Speed sensor	Concave Extension without end cover, 19-tooth Inch Internal Spline, With Temp.& Speed sensor	Square Flange Connection, Internal Spline(m=1,z=18), With Speed sensor	Concave Extension without end cover, Internal Spline (m=1,z=24)	Concave Extension without end cover, Internal Spline (m=1.125,z=20)

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (4KW II)

Model	XQ-4-3H	XQ-4-3HV	XQ-4-4AHV	XQ-4-7HV	XQ-12HV	XQ-4-13HV
R.P KW	4					
R.V V	48			72	48	
R.C A	102			67	102	
R.P.M	1700		2500	2800	3050	2540
Rating Min	60					
Protection Lv.	IP44		IP20	IP44		IP20
Application	ATV, 6-8Seats Tour-Bus					
Structure Features(Shaft Extension & Connection)	Concave Extension without end cover, 19-tooth Inch Internal Spline	Concave Extension without end cover, 19-tooth Inch Internal Spline, With Speed sensor	Square Flange Connection, Internal Spline (m=1,z=18), With Speed sensor	Concave Extension without end cover, 19-tooth Inch Internal Spline, With Speed sensor	Concave Extension without end cover, Internal Spline (m=1,z=24), With Speed sensor	Square Flange Connection, Internal Spline (m=1,z=18), With Speed sensor

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (5KW I)

Model	XQ-4HV	XQ-4HUV	XQ-4AH2V	XQ-4BH	XQ-4GHV
R.P KW	5				
R.V V	45				
R.C A	139				
R.P.M	1480				
Rating Min	60				
Protection Lv.	IP20				
Application	11-14Seats Tour-Bus				
Structure Features(Shaft Extension & Connection)	Spline(6-28x23x6)	Spline(6-28x23x6), With Speed sensor	Spline(6-28x23x6), With lead-wires	Horizontal with foot base, Spline(6-28x23x6)	Spline(6-28x23x6), Brush holder cover with 3 bracket screw holes

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (5KW II)

Model	XQ-5-5H	XQ-5-5HV	XQ-5-5BH	XQ-5-5CH	XQ-5-5GH	XQ-5-5GHV
R.P KW	5					
R.V V	67					
R.C A	93					
R.P.M	1500					
Rating Min	60					
Protection Lv.	IP20					
Application	11-14Seats Tour-Bus					
Structure Features(Shaft Extension & Connection)	Spline (6-28×23×6)	Spline (6-28×23×6), With Speed sensor	Horizontal with foot base, Spline (6-28×23×6), With locking Nuts	Horizontal with foot base, Spline (6-28×23×6)	Spline (6-28×23×6), Brush holder cover with 3 bracket screw holes	Spline (6-28×23×6), Brush holder cover with 3 bracket screw holes , With Speed sensor

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (5KW III)

Model	XQ-5-6H	XQ-5-7H	XQ-5-17HV
R.P KW	5		
R.V V	45	72	
R.C A	139	84	
R.P.M	1800	2800	3750
Rating Min	60		
Protection Lv.	IP20		
Application	8-14Seats Tour-Bus		
Structure Features(Shaft Extension & Connection)	Spline(6-28×23×6)	Concave Extension without end cover,19-tooth Inch Internal Spline	Concave Extension without end cover, Internal Spline(m=1,z=24), With Speed sensor

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (5KW IV)

Model	XQ-5-7HV	XQ-5-7BH	XQ-5-7BHV	XQ-5-7EHV
R.P KW	5			
R.V V	72			
R.C A	84			
R.P.M	2800			
Rating Min	60			
Protection Lv.	IP20			
Application	8-11Seats Tour-Bus			
Structure Features(Shaft Extension & Connection)	Concave Extension without end cover, 19-tooth Inch Internal Spline, With Speed sensor	Concave Extension without end cover, Internal Spline(m=1,z=24)	Concave Extension without end cover, Internal Spline(m=1,z=24), With Speed sensor	Concave Extension without end cover, Internal Spline (m=1.125,z=20), With Speed sensor

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (5.5KW)

Model	XQ-5.5H	XQ-5.5AHV
R.P KW	5.5	
R.V V	45	72
R.C A	152	91
R.P.M	1250	2482
Rating Min	60	
Protection Lv.	IP44	
Application	11-14Seats Tour-Bus	8-11Seats Tour-Bus
Structure Features(Shaft Extension & Connection)	Spline(6-32×26×6)	Concave Extension without end cover, 19-tooth Inch Internal Spline, With Speed sensor

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (6.3KW)

Model	XQ-6.3-3H	XQ-6.3-3HV	XQ-6.3-3BH	XQ-6.3-4H	XQ-6.3-6H	XQ-6.3-6AH
R.P KW	6.3					
R.V V	67			90	72	
R.C A	113			84	105	
R.P.M	1500			2000		
Rating Min	60					
Protection Lv.	IP20				IP44	
Application	14-19Seats Tour-Bus, Low Speed Electromobile					
Structure Features(Shaft Extension & Connection)	Spline (6-28×23×6)	Spline (6-28×23×6), With Speed sensor	Horizontal with foot base, Spline (6-28×23×6),	Spline (6-28×23×6)	Internal Spline (m=1,z=20)	Spline (6-28×23×6)

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (7.5-8.5KW)

Model	XQ-7.5-1H	XQ-8.5H	XQ-8.5AH	XQ-8.5AHV
R.P KW	7.5	8.5		
R.V V	90	72		
R.C A	100	138		
R.P.M	2000	2955	2970	
Rating Min	60			
Protection Lv.	IP20	IP44		
Application	21Seats Tour-Bus, Low Speed Electromobile			
Structure Features(Shaft Extension & Connection)	Spline(6-28×23×6)	Internal Spline(m=1,z=20)	Spline(6-28×23×6)	Spline(6-28×23×6), With Speed sensor

DC SERIES-EXCITAITION MOTORS FOR TOUR BUS (10KW)

Model	XQ-10H	XQ-10HV	XQ-10-1H	XQ-10-1HV
R.P KW	10			
R.V V	72		75	
R.C A	165		160	
R.P.M	1800		1200	
Rating Min	60			
Protection Lv.	IP20			
Application	Electric Sightseeing Train			
Structure Features(Shaft Extension & Connection)	Spline(6-32×26×6), With Lead-Wires	Spline(6-32×26×6), With Lead-Wires & Speed sensor	Spline(6-32×28×7), With Lead-Wires	Spline(6-32×28×7), With Lead-Wires & Speed sensor